

Features of Banko Tubine Grinders

- Quieter than vane machines
- Fewer moving parts
- Absolutely oil free
- Grease lubricated gearbox to eliminate oil leaks
- High power to weight ratio
- High productivity
- Long service intervals



Order Code	GTB31 A12 DW	GTB31 A85 DW
Model	Banko T3 Angle	Banko T3 Angle
Max. Free speed r/min	12000	8500
Spindle thread	M14	M14
Grinding wheel max. Mm	125	180
Max. power KW	3.4	3.4
Weight kg	2.6	2.6
Length mm	338	338
Recommended hose mm	Ø13	Ø13
Air inlet thread BSP	½	½
Optimal pressure bar	6,3	6,3
Air consumption max/min (l/sec)	45/14	45/14
Air exhaust	Sideway exhaust	Sideway exhaust
Sound level at free speed dB(A)	78	79
Vibration level	<3 m/s ²	<3 m/s ²



Order Code	GTB41 A85 DW	GTB31 A85 DW
Model	Banko T4 Angle	Banko T4 Angle
Max. Free speed r/min	8500	6600
Spindle thread	M14	M14
Grinding wheel max. Mm	180	230
Max. power KW	4.8	4.8
Weight kg	3.2	3.2
Length mm	337	337
Recommended hose mm	Ø16	Ø16
Air inlet thread BSP	½	½
Optimal pressure bar	6,3	6,3
Air consumption max/min (l/sec)	62/18	62/19
Air exhaust	Sideway exhaust	Sideway exhaust
Sound level at free speed dB(A)	87	87
Vibration level	<3,5 m/s ²	<3,5 m/s ²