

IMPACT DRIVERS

SI-1060



6MM STRAIGHT IMPACT DRIVER

DOUBLE HAMMER CLUTCH / REAR EXHAUST
/ REVERSIBLE

SCREW CAPACITY	6mm
MAX TORQUE	65Nm/48ft lb
AV. AIR CONS	83L/min 2.9cfm
AIR INLET SIZE	¼"NPT
NET WEIGHT	0.87kg
WIDTH	40mm

A powerful lightweight tool with hard hitting double hammer mechanism. Used for assembly work on small manufactured items such as electric appliances, engine components, electric motors and many other light assembly applications. Can be suspended from an overhead tool balancer.



SI-1301D

**NEW
MODEL**



AVAILABLE SOON

6MM STRAIGHT IMPACT DRIVER

DOUBLE HAMMER CLUTCH
/ BUTTERFLY THROTTLE / REVERSIBLE

SCREW CAPACITY	6mm
MAX TORQUE	55Nm/40ft lb
AV. AIR CONS	74L/min 2.6cfm
AIR INLET SIZE	¼"NPT
NET WEIGHT	0.68kg
WIDTH	

Butterfly throttle with instant reverse for single handed work in tight areas, ideal for light assembly and small engine work



IMPACT DRIVERS

SI-1370D

8MM STRAIGHT IMPACT DRIVER

DOUBLE HAMMER CLUTCH
/ MUFFLED EXHAUST / REVERSIBLE

SCREW CAPACITY	8mm
MAX TORQUE	80Nm/59ft lb
AV. AIR CONS	122L/min 4.3cfm
AIR INLET SIZE	¼"NPT
NET WEIGHT	1.21kg
WIDTH	48mm

Powerful double hammer tool with silencer. Designed for overhead suspension with palm grip throttle operation. Larger capacity and heavier duty than SI-1060 and SI-1301D.



SI-1065

6MM PISTOL IMPACT DRIVER

DOUBLE HAMMER CLUTCH / HANDLE EXHAUST
/ REVERSIBLE

SCREW CAPACITY	6mm
MAX TORQUE	65Nm/48ft lb
AV. AIR CONS	96L/min 3.4cfm
AIR INLET SIZE	¼"NPT
NET WEIGHT	0.98kg
WIDTH	40mm

A powerful compact lightweight pistol grip, double hammer impact driver for assembly and dis-assembly work.



SI-1070

**NEW
MODEL**

6MM PISTOL IMPACT DRIVER

DOUBLE HAMMER CLUTCH

SCREW CAPACITY	6mm
MAX TORQUE	35Nm/25ft lb
AV. AIR CONS	60L/min 2.1cfm
AIR INLET SIZE	¼"NPT
NET WEIGHT	0.37kg
WIDTH	

Compact, lightweight tool for general assembly work. Moulded rubber hand grip reduces vibration, adds comfort and insulates operators hand in cold conditions. "Feather Touch" trigger for easy operation.



SI-1356D

8MM PISTOL IMPACT DRIVER

DOUBLE HAMMER CLUTCH /
FRONT EXHAUST / REVERSIBLE

SCREW CAPACITY	8mm
MAX TORQUE	55Nm/40ft lb
AV. AIR CONS	77L/min 2.7cfm
AIR INLET SIZE	¼"NPT
NET WEIGHT	1.22kg
WIDTH	46mm

Used for assembly work in the manufacture and repair of small engines, lawn mowers, pumps, trowelling machines and many other applications and in assembly of slotted angle racking and shelving subject to torque requirements. Used in the furniture manufacturing industry for driving screws into particleboard where fine control is needed and no torque reaction is wanted.



SI-1365D

8MM PISTOL IMPACT DRIVER

DOUBLE HAMMER CLUTCH / MUFFLED
EXHAUST / REVERSIBLE

SCREW CAPACITY	8mm
MAX TORQUE	70Nm/51ft lb
AV. AIR CONS	94L/min 3.3cfm
AIR INLET SIZE	¼"NPT
NET WEIGHT	1.32kg
WIDTH	55mm

A compact tool with a double hammer impact mechanism which gives it a high power-to-weight ratio for industrial use. The exhaust is through the handle for quieter operation. Uses as for SI-1356D but where more power is required.

