


## GRINDERS – BENCH

### 66VBG;6000;9



#### 200MM HIGH SPEED BENCH GRINDER

STEEL FRAME / ALUMINIUM MOTOR HOUSING /  
ADJUSTABLE SPARK ARRESTOR / ADJUSTABLE WORK  
REST

FREE SPEED	6000rpm
SPINDLE DIA	15.88mm
MAX. WHEEL SIZE	235 X 25 X 15.88
POWER	3000W 4HP
MAX. AIR CONS	2124L/Min 75cfm
AIR INLET SIZE	½" NPT
AIR HOSE REQD	13mm ½" I.D.
NET WEIGHT	23.5kg

Strong, powerful, compact machine ideal for use in harsh exposed environments such as mineral exploration sites, ship yards, open cut mines, and heavy fabrication shops. Uses high speed hand grinder wheels.



### 662VBG;3300;9



#### 200MM LOW SPEED BENCH GRINDER

STEEL FRAME / ALUMINIUM MOTOR HOUSING /  
ADJUSTABLE SPARK ARRESTOR / ADJUSTABLE WORK  
REST

FREE SPEED	3300rpm
SPINDLE DIA	15.88mm
MAX. WHEEL SIZE	235 X 25 X 25
MAX. BRUSH SIZE	235 X 25 X 25
POWER	3000W 4HP
MAX. AIR CONS	2124L/Min 75cfm
AIR INLET SIZE	½" NPT
AIR HOSE REQD	13mm ½" I.D.
NET WEIGHT	26kg

Similar to 66VBG but geared down to slower speed to allow the use of both grinding wheels and wire brushes. Applications are the same as 66VBG.

