

PILE CUTTERS


56PCK;6000;841

200MM PILE CUTTER

SAFETY LEVER THROTTLE

WHEEL SIZE	200mm x 22.2CH
POWER	2250W 3.0HP
OUTPUT SHAFT	5/8"-11
FREE SPEED	6000rpm
MAX. AIR CONS	1699L/Min 60cfm
AIR INLET SIZE	½"NPT
AIR HOSE REQD	13mm ½"I.D.
NET WEIGHT	3.9kg

Used by Marine and Bridge Contractors. Takes bonded abrasive or segmented diamond wheels. Wet attachment optional.



186mm



66PCK;5000;1241

300MM PILE CUTTER

SAFETY LEVER THROTTLE

WHEEL SIZE	300mm x 22.2CH
POWER	3000W 4.0HP
OUTPUT SHAFT	5/8"-11
FREE SPEED	5000rpm
MAX. AIR CONS	2124L/Min 75cfm
AIR INLET SIZE	½"NPT
AIR HOSE REQD	20mm ¾"I.D.
NET WEIGHT	5kg

Same use as 56PCK;841 but takes 12" bonded abrasive or segmented diamond wheels for greater depth of cut. For same model with 6000rpm order 66PCK;6000;1241. Wet attachment optional.



202mm



66PCK;4000;1441

350MM PILE CUTTER

SAFETY LEVER THROTTLE

WHEEL SIZE	350mm x 22.2CH
POWER	3000W 4.0HP
OUTPUT SHAFT	5/8"-11
FREE SPEED	4000rpm
MAX. AIR CONS	2124L/Min 75cfm
AIR INLET SIZE	½"NPT
AIR HOSE REQD	20mm ¾"I.D.
NET WEIGHT	5.5kg

Same as 66PCK;1241 but takes 14" bonded abrasive or segmented diamond wheels for greater depth of cut. For same model with 5000rpm order 66PCK;5000;1441. Wet attachment optional.



202mm

